

PERMASHELL[®], FILTER, COVER & CABINET CARE MAINTENANCE

Western Red Cedar

As with any wood product, maintaining the "new" look requires a consistent schedule of treating your cabinet with a quality CEDAR sealing product.

Permawood[®] – Cape Cod Grey, Teak, Pecan

Maintenance for Permawood[®] is to use mild soap and water. Some strong household cleaners/solvents can cause damage/fading to the surface of the cabinet. All cleaners should be tested on an out-of-the-way section of cabinet before cleaning.

PERMASHELL® continued

PermaShell®

PermaShell® cleans very easy because of its durable poly material. A spray cleaner that is low in "suds" and is applied then wiped off will most of the time be sufficient. With stubborn stains or marks, a "soft" scrub cleaner with very low abrasion (elements) will help when used with a non-abrasive cleaning pad.

Cover or Hot Tub Lid

See manufacturer's warranty and maintenance procedures. **When using a spa or hot tub "shock" water treatment, the cover must be removed for 30 minutes. Failure to remove cover may cause damage to cover.**

Filters

Periodic filter maintenance is required in order to maintain proper hot tub water quality and performance of equipment supplied with this hot tub. The manufacturer recommends cleaning your filters with high pressure water flow once a week. Once a month it is recommended that filters be soaked in a quality filter cleaning solution before high pressure spraying of the filter cartridge is applied. **It is important to follow all chemical manufacturers instructions.**

The use of any spa sanitizer with the exception of dichlor chlorine will negate your warranty.